

# TECHNICAL DATA SHEET: TRANSITION PIECE FROM QF/FB

Ø mm	Flat Edge mm	Steel Thickness mm	Weight kg
80	6	0,7	0,1
100	6	0,7	0,1
125	6	0,7	0,1
140	6	0,7	0,1
150	6	0,7	0,2
160	6	0,7	0,2
180	6	0,7	0,2
200	6	0,7	0,3
224	6	0,7	0,3
250	6	0,7	0,3
300	6	0,7	0,4
315	6	0,7	0,4
350	6	0,7	0,4
400	6	0,9	0,5
450	6	0,9	0,6
500	6	0,9	0,6
630	6	0,9	1,0



### Construction:

**Ends:** 6 mm turned out edge (FB).

### Additional Notes

At temperatures ranging between 200° C and 250° C, the zinc-iron alloy layers in galvanised steel will continue to provide a high level of protection from corrosion. However, there may be some peeling, changes in mechanical properties, and reduction in the corrosion protection. Recommended max. service temperature is +80°C. Stainless Steel available upon request.

### Compliance / Rating of Product Components

Product	Material	Compliance / Rating
Transition Piece QF/FB	Galvanised	DX51D with Z275 Coating
Joka Seal Metal Sealant 2315	Aceton Blend	AAMA Specification 801.1

### Temperature Rating of Product Components

	Transition Piece QF/FB	Sealant
200°C	Galvanised Steel	Joka Seal Metal Sealant 2315
121°C		
-20°C		

