

TECHNICAL DATA SHEET: ROGD & ROGE MILD STEEL TRANSITION

Ø A mm	ROGD Transition from round to rectangular				ROGE Transition from round to rectangular			
	Steel Thickness mm	L	W	H	Steel Thickness mm	L	W	H
Manufactured to customers request. Specify Ø and L x W x H	2	X	X	X	3	X	X	X

ROGD = 2 mm steel thickness.
ROGE = 3 mm steel thickness.



Compliance / Rating of Product Components

Product	Material	Compliance / Rating
Welded ROGD & ROGE Transition	Mild Steel	S235JR/EN

Temperature Rating of Product Components

Welded ROGD & ROGE Transition	
200°C	Mild Steel Base and Top Coat RAL 7032 grey
-20°C	

Additional Notes

- Mild Steel quality S235JR/EN. Stainless Steel quality EN.14301/EN. Other steel qualities available upon request.
- Base and top coat in RAL 7032 grey, 50 microns. Other colors available upon request.
- Max. working temperature of the surface treatment is +200°C.
- Recommended max. service temperature is +80°C.
- Manufactured to customers request, please specify Ø and L x W and H.
- ROGD is available in Ø 100 - 1250 mm.
- ROGE is available in Ø 150 - 1250 mm.

