

| Ø mm | Minimum Ø mm | Supplied Ø mm | Band Thickness mm | Rec. tightening torque Nm |
|---------|--------------|---------------|-------------------|---------------------------|
| 50-65 | 50 | 66 | 1,0 | 5-6 |
| 58-75 | 58 | 76 | 1,0 | 5-6 |
| 68-85 | 68 | 86 | 1,0 | 5-6 |
| 77-95 | 77 | 96 | 1,0 | 5-6 |
| 87-112 | 87 | 113 | 1,0 | 5-6 |
| 106-138 | 106 | 139 | 1,0 | 5-6 |
| 132-165 | 132 | 166 | 1,0 | 5-6 |
| 150-180 | 150 | 181 | 1,0 | 5-6 |
| 175-205 | 175 | 206 | 1,0 | 5-6 |
| 200-231 | 200 | 232 | 1,0 | 5-6 |
| 226-256 | 226 | 257 | 1,0 | 5-6 |
| 251-282 | 251 | 283 | 1,0 | 5-6 |
| 277-307 | 277 | 308 | 1,0 | 5-6 |



Construction:

Screw: Electro zinc plated.

Band: Aluzink.

Housing: Painted.

Compliance / Rating of Product Components

| Product | Material | Compliance / Rating |
|------------|------------|-------------------------|
| Hose Clamp | Galvanised | DX51D with Z275 Coating |

Temperature Rating of Product Components

| | Hose Clamp |
|--------------------------------|------------------|
| 200°C | Galvanised Steel |
| 70°C (intermittent to 90°C) | |
| -20°C | |

