


# TECHNICAL DATA SHEET: QUICK-FIT (QF) MACHINE ADAPTER

Ø A mm	O/D A mm	I/D A mm	Rolled Edge (nom. mm)	Length (nom. mm)	Weight kg	Galvanised Steel Thickness mm
080	79	78	6	130	0,1	0,7
100	98	97	6	130	0,1	0,7
125	124	123	6	130	0,2	0,7
140	139	138	6	130	0,3	0,7
150	148	147	6	130	0,3	0,7
160	159	158	6	130	0,3	0,7
180	179	178	8	130	0,3	0,7
200	200	199	8	130	0,4	0,7
224	224	223	8	130	0,4	0,7
250	250	249	8	130	0,4	0,7
300	298	297	10	130	0,5	0,7



## Compliance / Rating of Product Components

Product	Material	Compliance / Rating
Quick-Fit (QF) Machine Adapter	Galvanised 304 / 316 Stainless Steel	DX51D with Z275 Coating EN.1.4301/TP.304
Joka Seal Metal Sealant 2315	Aceton Blend	AAMA Specification 801.1

## Temperature Rating of Product Components

	Quick-Fit (QF) Machine Adapter	Sealant
<b>593°C</b>		
<b>200°C</b>		
<b>121°C</b>	Galvanised Steel	304 / 316 Stainless Steel
<b>-20°C</b>		Joka Seal Metal Sealant 2315

## Additional Notes

At temperatures ranging between 200° C and 250° C, the zinc-iron alloy layers in galvanised steel will continue to provide a high level of protection from corrosion. However, there may be some peeling, changes in mechanical properties, and reduction in the corrosion protection. Recommended max. service temperature is +80°C. Stainless Steel available upon request.

