


TECHNICAL DATA SHEET: QUICK-FIT (QF) VENTILATION ADAPTER

Ø mm	O/D mm	I/D mm	Rolled Edge (nom. mm)	Length (nom. mm)	Weight kg	Galvanised Steel Thickness mm
080	79	78	6	116	0,2	0,7
100	98	97	6	116	0,2	0,7
125	124	123	6	116	0,2	0,7
140	139	138	6	116	0,3	0,7
150	148	147	6	116	0,3	0,7
160	159	158	6	116	0,3	0,7
180	179	178	8	116	0,3	0,7
200	200	199	8	116	0,4	0,7
224	224	223	8	116	0,4	0,7
250	250	249	8	116	0,5	0,7
300	298	297	10	116	0,5	0,7
315	313	312	10	116	0,6	0,7
350	348	347	10	116	0,7	0,9
400	400	398	10	116	1,1	0,9
450	449	447	10	116	1,2	0,9
500	499	497	10	116	1,4	0,9
560	559	557	10	116	1,5	0,9
630	629	627	10	116	1,7	0,9
710	709	707	10	116	1,9	0,9



Ends: QF (Quick-Fit rolled edge)

Additional Notes

At temperatures ranging between 200° C and 250° C, the zinc-iron alloy layers in galvanised steel will continue to provide a high level of protection from corrosion. However, there may be some peeling, changes in mechanical properties, and reduction in the corrosion protection. Recommended max. service temperature is +80°C. 304 Stainless Steel is available in Ø80-500, with 0,7 mm steel thickness. 316 Stainless Steel available upon request.

Compliance / Rating of Product Components

Product	Material	Compliance / Rating
Quick-Fit (QF) Ventilation Adapter	Galvanised 304 Stainless Steel	DX51D with Z275 Coating EN.1.4301/TP.304
Joka Seal Metal Sealant 2315	Aceton Blend	AAMA Specification 801.1

Temperature Rating of Product Components

	Quick-Fit (QF) Ventilation Adapter	Sealant
593°C		
200°C		
121°C	Galvanised Steel	304 Stainless Steel
-20°C		Joka Seal Metal Sealant 2315

